

0.2 LIST OF EFFECTIVE PAGES

Section	Page	Date	Section	Page	Date
0	1	03.02.2012	2	5	03.02.2012
	2	16.03.2015		6	03.02.2012
	3	16.03.2015		7	03.02.2012
	4	03.02.2012		8	03.02.2012
	5	03.02.2012		9	03.02.2012
1				10	03.02.2012
	1	03.02.2012		11	03.02.2012
	2	03.02.2012		12	03.02.2012
	3	03.02.2012		14	03.02.2012
	4	03.02.2012			
	5	03.02.2012	3	1	03.02.2012
	6	03.02.2012		2	03.02.2012
	7	03.02.2012		3	03.02.2012
	8	03.02.2012		4	03.02.2012
	9	03.02.2012		5	03.02.2012
	10	03.02.2012		6	03.02.2012
	11	03.02.2012		7	03.02.2012
	12	03.02.2012		8	03.02.2012
	13	03.02.2012		9	03.02.2012
	14	03.02.2012		10	03.02.2012
	15	03.02.2012		11	03.02.2012
	16	03.02.2012		12	03.02.2012
	17	03.02.2012		13	03.02.2012
	18	16.03.2015		14	03.02.2012
	19	03.02.2012		15	03.02.2012
	20	03.02.2012		16	03.02.2012
	21	03.02.2012		17	03.02.2012
	22	03.02.2012		18	03.02.2012
	23	03.02.2012		19	03.02.2012
	24	03.02.2012		20	03.02.2012
	25	03.02.2012		21	03.02.2012
	26	03.02.2012		22	03.02.2012
	27	03.02.2012		23	03.02.2012
	28	03.02.2012		24	03.02.2012
	29	03.02.2012		25	03.02.2012
	30	03.02.2012		26	03.02.2012
	31	03.02.2012			
	32	03.02.2012	4	1	03.02.2012
				2	03.02.2012
2	1	03.02.2012		3	03.02.2012
	2	03.02.2012		4	03.02.2012
	3	03.02.2012		5	03.02.2012
	4	03.02.2012		6	03.02.2012

Powerplant instrument markings and their colour code significance are shown below:

Instrument	Unit	Red Line Minimum Limit	Green Arc Normal Operating	Yellow Arc Caution Range	Red Line Maximum Limit
Tachometer	RPM	1400	1800 - 5500	5500 - 5800	5800
Manifold pressure	inHg	-	10,0 – 35,4 ³	35,4 – 39,9 ³	39,9 ³
Oil temperature indicator	°C	50	90 - 110	50 - 90 110 – 130 ^{1,3} 110 – 140 ²	130 ^{1,3} 140 ²
Coolant temperature indicator	°C	-	90 – 110	50 – 90 110 – 120	120
Cylinder head temperature indicator	°C	-	-	-	135 ^{1,3} 150 ²
Fuel pressure indicator	bar	0,15	0,20 - 0,35	0,15 - 0,20 0,35 - 0,40	0,40
Oil pressure indicator	bar	0,8	2,0 - 5,0	0,8 - 2,0 5,0 - 7,0	7,0
Fuel quantity indicator	l	Red light annunciator will be illuminated with the remaining 7 litres of fuel in the fuel tank.			

- 1) Indication is valid for ROTAX 912 S2 engine
 2) Indication is valid for ROTAX 912 UL engine
 3) Indication is valid for ROTAX 914 F/UL engine

1.6.8.4. Avionics

The following avionics are mounted in the airplane: radios and intercom. This equipment must be connected with the headphones and with the antenna. The airplane might be equipped with other instruments (GPS, transponder, or board computer). The flight and navigation instruments are mounted as an option of the customer (but with respect to the weight limitation of the aircraft). Refer to the Manuals supplied with above mentioned instruments for right operation of the instruments and for more details.

1.6.8.5. Rescue system

The airplane can be equipped with parachute rescue system MAGNUM 601 S-LSA from the company STRATOS 07 spol. s r. o. as miscellaneous equipment. This rescue system is designed for the aircraft with maximum weight up to 620 kg and with maximum speed of using 290 km/h. The area of parachute is 130 m². The descent rate with opened parachute is 7,0 m/sec. The container dimension is 430x210x250 mm and the total weight is 12,9 kg. Rocket motor is Magnum 600 A with total thrust pulse 0,539 kNs. The life time of the rescue system is 18 years with the repacking interval is 6 years.



Fig. 10. Rescue system MAGNUM 601 S-LSA